

PakMix® SAND MIX

PakMix® Sand Mix is a specially formulated blend of Portland cement and sand ideal for use where a thickness of 1" to 2" is required. All ingredients are thoroughly premixed to ensure maximum strength and workability. Simply add water.



Product Name:

PakMix® Sand Mix

Distributor:

Consolidated Aggregates
1205 Palestine Road
Picayune, MS 39466
601-798-3158

Weight and Size (s):

60 lb., 80 lb., and 3000 lb. Bulk Bags

Color: Gray

Features/Benefits:

- ◆ Easy to use for the do it yourselfer on home projects.
- ◆ Quality product that meets ASTM C-387 Standard.
- ◆ Cost effective for both small and large projects.

Applications:

- ◆ Concrete floor topping
- ◆ Filling cracks
- ◆ Parging
- ◆ Stuccoing
- ◆ Repairing walls and floors
- ◆ Grouting
- ◆ Filling tree cavities
- ◆ Laying flagstones and paving brick

Coverage/Yield for Usage:

- ◆ 60 lb. bag yields approximately 6 sq. ft. x 1" thick or 1/2 cu. ft. wet volume.

Technical Information:

- ASTM C-387 Standard Specification for Packaged, Dry, Combined Materials for Concrete

Mixing Instructions:

Pour the necessary amount of Pakmix® Sand Mix into a clean wheelbarrow, mortar box or similar easy-to-use container. Form a crater with a shovel or hoe in the center of the dry mix. Pour clean water into the crater at the rate of approximately 1 quart per 15 lbs. of dry material. If the mix is too stiff, add more water one cup at a time. Too much water will weaken the mix.

NOTE: Use only when the temperature is 40° F or above. In cold weather use warm, not hot, water for mixing. Apply freshly mixed Pakmix® Sand Mix immediately. Do not re-temper the mix after initial mixing. When patching or resurfacing it is important to dampen the surface of the existing concrete before applying the new material. The use of Pakmix® Cement Fortifier and Pakmix® Concrete Glue for enhanced bonding is beneficial. The use of Pakmix® Cure & Seal is recommended. Allow the new concrete to set firmly then keep moist for at least 3 days by an occasional fine spraying with water. Covering the area with plastic film or damp burlap is recommended.

PakMix® SAND MIX

Clean Up:

Clean-up is easy with soap and water. Rinse the tools before the material hardens.

Cautions:

Avoid contact with skin and eyes. Contains Portland Cement (CAS #65997-15-1). Freshly mixed cement, mortar, concrete or grout may cause skin injury including severe alkali burns. If exposed, wash skin promptly and repeatedly for 15 minutes and get prompt medical attention. The use of gloves and protective eyewear is recommended.

Freeze/Thaw Warning:

This product is not air entrained and may be susceptible to freeze/thaw damage. Contact Pakmix for air entrainment recommendations.

Safety:

READ AND UNDERSTAND ALL THE INFORMATION ON THE SAFETY DATA SHEET (SDS) BEFORE USING THIS PRODUCT.

SDS sheets are available at our website
www.consolidatedagg.com.

WARNING: Wear protective clothing and equipment.

KEEP OUT OF REACH OF CHILDREN.

