

SECTION 1 – CHEMICAL PRODUCT AND COMPANY INFORMATION

PRODUCT NAME: Industrial Sand	MANUFACTURER: Consolidated Aggregates
PRODUCT USE: Concrete Sand, Masonry Sand, Filter Sand, Geothermal Well	1205 Palestine Road
Drilling Sand, Railroad Traction Sand, All Purpose Commercial Sand,	Picayune, MS 39466 (UA)
Polymeric Sand, Non-Skid Safety Sand, Pure Sand Burlap Bags, All Purpose Gravel.	TEL: 601-798-3158 E: info@consolidatedaggregates.com
EMERGENCY: Call Poison Control	MEDICAL: Call 911

SECTION 2 – Composition/ Information of Ingredients

Hazardous Ingredients	%	CAS #	LD 50	LC 50
Silica Quartz	99.3 – 99.6%	14808-60-7		

SECTION 3 – HAZARDOUS IDENTIFICATION

Components	CAS #	EC #	Concentration, %
Silica Quartz	14808-60-7	n/a	

Route of Entry	Eye contact, skin contact, inhalation, and ingestion.
Eyes	Eye exposure to silica quartz can cause slight irritations as a foreign object. Tearing, Blinking and mild temporary pain may occur.
Skin	May cause skin irritation.
Inhalation	Prolonged exposure to respirable crystalline silica may aggravate other lung conditions. It may also cause delayed lung injury, including silicosis, cancer, tuberculosis, and/or other diseases.
Ingestion	Crystalline silica or quartz is non-toxic having no know adverse health effects from Ingestion.

PICTOGRAMS:



SECTION 4 – FIRST AID MEASURES

<p>EMERGENCY INFORMATION: The adverse health effects from crystalline silica exposure-silicosis, cancer, scleroderma, tuberculosis, and nephrotoxicity- are chronic effects.</p>	<p>EYES: Immediately flush eye thoroughly with water. Continue flushing eye for at least 15 minutes, including under lids, to remove all particles.</p> <p>SKIN: If on the skin or clothing remove and wash all exposed skin with water for at least 15 minutes.</p> <p>INHALATION: Remove person to fresh air. If breathing is difficult, get medical attention.</p> <p>INGESTION: If swallowed rinse mouth thoroughly. Do not induce vomiting without the advice from the poison control center of medical professional. Get medical assistance if you feel unwell.</p>
---	---

SECTION 5 – FIREFIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA:	Use an extinguishing agent suitable for the surrounding fire.
UNSUITABLE EXTINGUISHING MEDIA:	Do not use water jet and halogenated compounds
SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:	This product is non-flammable and non-combustible. Containers at risk from fire should be cooled with water spray and, if possible, removed from the danger area.
HAZARDUS COMBUSTION PRODUCTS:	None.
SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS:	Firefighters should wear full protective gear.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES:	Keep unnecessary and unprotected personnel from entering spill area. Do not touch or walk through spilled material.
PROTECTIVE EQUIPMENT:	Use exposure control and personal protection methods as described in Section 8. Ensure adequate ventilation/exhaust extraction. Avoid inhalation of dust and contact with skin and eyes during clean up.
PROPER METHODS OF CONTAINMENT:	Collect dry material using a scoop. Avoid actions that cause dust to become airborne. Do not dry sweep. Avoid inhalation of dust and contact with skin. Vacuum dust with equipment fitted with HEPA filter and place in a designated labeled waste container. If material is wet, scrape up wet material and place in an appropriate container. Allow the material to dry before disposal. For major spills: approach from upwind. Prevent wind dispersal.
CLEANUP:	Seal the container(s), remove from spill area, and properly dispose of the waste material in accordance with existing federal, state, and local regulations.
ENVIRONMENTAL PRECAUTIONS:	Prevent from entering soil, ditches, sewers, waterways and/or groundwater, basements, or confined areas. Large spills in waterways may be hazardous due to alkalinity of the certain components of the product. Inform the relevant authorities if the product has accessed waterways or other natural areas. See Section 12 for more details.

SECTION 7 – HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING:	Do not breathe dust. Use adequate ventilation and/or dust collection methods. Use all available work practices to control dust exposures, such as water sprays. Do not permit dust to collect on walls, floors, sills, ledges, machinery, or equipment. Avoid breakage of bagged material or spills of bulk material. Wear appropriate respiratory, eye and skin protection. Avoid contact with skin and eyes. Wash hands thoroughly after handling. Eating, drinking, and smoking should be prohibited in areas where this material is managed, stored, and processed. Hands and/or face should be washed before eating, drinking, and smoking and at the end of the shift. Remove contaminated clothing and protective equipment before entering eating areas. Wash or vacuum clothing when becomes dusty. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure by obtaining and following special instructions before use. Do not handle until all safety precautions have been read and understood.
PRECAUTIONS FOR STORAGE:	Store in original or approved alternative container protected from direct sunlight in a dry, cool, and well-ventilated area away from incompatible materials (see below for details) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed. Store bags to avoid accidental tearing, breaking, or bursting. Avoid windblown dust by shielding or covering outdoor stockpiles. Protect from getting wet from atmospheric moisture and other sources.
INCOMPATIBILITIES:	- Silica reacts violently with powerful oxidizing agents such as hydrofluoric acid, fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, oxygen difluoride, hydrogen peroxide, acetylene, ammonia yielding fire and/or explosions. Silicates dissolve readily in hydrofluoric acid producing a corrosive gas silicon tetrafluoride.

SECTION 8 – PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

OSHA's PERMISSIBLE EXPOSURE LIMITS (PEL)

COMPONENTS	CAS #	OSHA PEL mg/m ^{3(e)}	Cal/OSHA PEL 8-hour TWA, mg/m ³	NIOSH REL Up to 10-hour TWA, mg/m ³	ACGIH 2017 TLV 8hrs TWA, mg/m ³
Silica Sand	14808-60-7	No Data	N/A	N/A	N/A

ENGINEERING CONTROLS:	Avoid actions that cause dust to become airborne. Use local exhaust or general dilution ventilation to control exposure within applicable limits.
------------------------------	---

PERSONAL PROTECTIVE EQUIPMENT (PPE).

RESPIRATORY PROTECTION:	Use local exhaust or general dilution ventilation to control dust levels below applicable exposure limits. Minimize dispersal of dust into air. If local or general ventilation is not adequate to control dust levels below applicable exposure limits or when dust causes irritation or discomfort, use MSHA/NIOSH approved respirators.
EYE PROTECTION:	Wear safety glasses with side shields or goggles to avoid contact with your eyes. In extreme dusty environments and unpredictable environments, wear tight fitting unvented or indirectly vented goggles to avoid eye irritation or injury. Contact lenses should not be worn when handling silica quartz.
SKIN PROTECTION:	Wear impervious abrasion and gloves, boots, long sleeve shirt, long pants, or other protective clothing to prevent skin contact.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

VISCOSITY	Not Applicable	APPEARANCE:	Grainy Sand
ODOR & ODOR THRESHOLD:	Odorless	FLASH POINT:	Not Applicable, Not Flammable, Not Combustible
BOILING POINT:	N/A	MELTING POINT:	N/A

EVAPORATION RATE:	Not Applicable	FLAMMABILITY (SOLID/GAS)	Not Applicable
VAPOR PRESSURE:	Not applicable	pH (IN WATER): (ASTM D 1293-95)	Not Applicable
VAPOR DENSITY:	Not applicable	SOLUBILITY IN WATER:	Slightly (0.1%-1.0%)
RELATIVE DENSITY	Not Applicable	UPPER/LOWER FLAMMABILITY	Not Flammable, Not Explosive
PARTITION COEFFICIENT:	Not Applicable	AUTO IGNITION TEMPERATURE	Not Flammable

SECTION 10 – STABILITY AND REACTIVITY

CHEMICAL STABILITY:	Product is stable under recommended storage conditions. Keep dry until used.		
CHEMICAL REACTIVITY:	Hazardous Polymerization:	Will not occur.	
	Corrosion to Metals:	Not Corrosive	
	Oxidizing Properties:	Not classified as oxidizing.	
CONDITIONS TO AVOID:	Unintentional contact with water or high humidity. Contact with water will result in hydration and produce (caustic) calcium hydroxide and heat. Avoid generation of dust.		
INCOMPATIBILITY:	<p>- Silica reacts violently with powerful oxidizing agents such as hydrofluoric acid, fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, oxygen difluoride, hydrogen peroxide, acetylene, ammonia yielding fire and/or explosions. Silicates dissolve readily in hydrofluoric acid producing a corrosive gas silicon tetrafluoride.</p>		
HAZARDOUS DECOMPOSITION:	Will not spontaneously occur. Adding water results in hydration and produces (caustic) calcium hydroxide. Under normal conditions of storage and use, hazardous decomposition products should not be produced. In fire conditions, depending on temperature, air supply and presence of other materials, decomposition products can include, but are not limited to carbon dioxide, carbon monoxide, silica oxides, sulfur oxides, metal oxides.		

SECTION 11 – TOXICOLOGY INFORMATION

ACUTE TOXICITY	INGESTION:	Harmful if swallowed.				
	INHALATION:	May cause respiratory tract irritation and coughing. Ingredients may contain trace amounts of crystalline silica. Exposure to these ingredients more than the applicable TLV or PEL (see Section 2) may cause or aggravate other lung conditions				
	SKIN CORROSION SKIN IRRITATION	Acute Skin Irritation.				
	SERIOUS EYE DAMAGE & IRRITATION	Dust may cause abrasion of the cornea.				
	SPECIFIC TARGET ORGAN GENERAL TOXICITY: SINGLE EXPOSURE:	This product contains components that may cause respiratory tract irritation after single exposure.				
	SPECIFIC TARGET ORGAN GENERAL TOXICITY: REPEAT EXPOSURE	Target Organ: Lungs.				
	ASPIRATION HAZARD:	Not an aspiration hazard.				
CLASSIFICATIONS:	Carcinogen	Skin Corrosion	Eye Damage	Skin Sensitization	STOT RE	STOT SE
Mixture	Cat 1A	Cat 1B	Cat 1	Cat 1B	Cat 1	Cat 3

Reproductive Toxicity:	Risk to humans is not expected from exposure to this product.
------------------------	---

General Product Warning:	May cause cancer. Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease and/or lung cancer. IARC states that crystalline silica in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (Group 1).
--------------------------	--

SECTIONS 12 – ECOLOGICAL INFORMATION

ECOTOXICITY	Not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
PERSISTENCE AND DEGRADABILITY:	No information available for the product, believed to be not readily biodegradable by OECD criteria.
BIOACCUMULATIVE POTENTIAL:	No information is available for the product, but it is believed that no significant accumulation in organisms is expected
MOBILITY IN SOIL:	No information is available for the product, but it is believed that mobility in soil is not expected

OTHER ADVERSE EFFECTS:	No information is available for the product
-------------------------------	---

SECTION 13 – DISPOSAL CONSIDERATIONS

PRODUCT DISPOSAL:	The generation of waste should be avoided or minimized wherever possible. If product becomes a waste, it does not meet criteria of hazardous waste as defined in 40 CFR 261, Subpart C and D. Do not discharge or dump material into sewer system, the ground, or bodies of water. Spill cleanup residues may still be subject to RCRA storage and disposal requirements. Dispose of waste in compliance with local, state, and federal regulations via licensed waste disposal contractor. See Section 7 for Handling Procedures. See Section 8 for Personal Protective Equipment recommendations
CONTAINER DISPOSAL:	Even after emptying, the container may retain residues. Containers should be completely emptied and safely stored until appropriately reconditioned or dispose of (contents/container) in accordance with local/regional/national/international regulations.

SECTION 14 – TRANSPORTATION CONSIDERATIONS

Land transport, U.S. DOT:	Non-Regulated
Sea transport, IMDG	Non-Regulated
Air transport, IATA/ICAO:	Non-Regulated

SECTION 15 – REGULATORY INFORMATION (Non-Mandatory Section as per OSHA: Not a Complete List)

U.S. REGULATIONS

OSHA HCS:	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29CFR 1910.1200.
TSCA REGULATIONS:	All components of this product are listed or are exempt from TSCA Inventory requirements under 40 CFR 720.30
EPCRA Section 302 (40 CFR Part 355)	(Emergency Response Planning, Extremely Hazardous Substance): No components are subject to the reporting.
EPCRA Section 304 (40 CFR Part 355)	(Emergency Release Notification Requirements): No components are subject to the reporting.
EPCRA Sections 311 & 312	(Hazardous Chemical Inventory Reporting, Hazard Categories): Acute Health Hazard, Chronic Health Hazard
EPCRA Section 313 40 CFR Part 372)	(Toxic Chemical Release Inventory Reporting): No components or impurities of this product are present above De Minimis level and therefore do not require reporting.
CERCLA Sections 102-103 (40 CFR Part 302)	(Hazardous Substances Release Notification): No components are subject to the reporting. Some of the components contain trace amounts of the following chemicals that require reporting if a criterion of reportable quantity is fulfilled: Fine Mineral Fibers of average diameter ≤1µm (including Crystalline Silica, CAS #: 14808-60-7 with diameter ≤1µm)
CLEAN AIR ACT	Ozone Depleting Substances (ODS): This product does not contain and is not manufactured with ozone depleting substances. Hazardous Air Pollutants, OSHA, Section 112(b), Table Z-1 and Table Z-3:

COMPONENT ANALYSIS - STATE

STATE	INFORMATION
CA	The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING! This product contains chemicals known to the state of California to cause cancer, birth defects, or other reproductive harm.

SECTION 16 – OTHER INFORMATION

HAZARDOUS MATERIAL INFORMATION SYSTEM (HMIS)
 NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme
 E-Protective Equipment: Safety glasses, gloves, Dust Respirator

Health	1
Flammability	0
Reactivity	0
Personal Protection	E

OTHER INFORMATION:

SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY CONSOLIDATED AGGREGATES, except that the product shall conform to contracted specifications. The information provided herein was believed by CONSOLIDATED AGGREGATES to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. Buyer's exclusive remedy shall be for damages and no claim of any kind, whether as to product delivered or for non-delivery of product, failure of product due to manufacturers defect, and whether based on contract, breach of warranty, negligence, or otherwise shall be greater in amount than the purchase price of the quantity of product in respect of which damages are claimed. In no event shall Seller be liable for incidental or consequential damages or labor of any kind, whether Buyer's claim is based on contract, breach of warranty, negligence, manufacturers defect, product failure, or otherwise.

Rest of Sheet Purposely Left Blank

END OF SHEET