

## PakMix® BLACKTOP PATCH

**PakMix® Blacktop Patch** is a ready-to-use mixture of asphalt and graded aggregates ideal for the repair of blacktop surfaces. Pre-blended; no mixing is required before use.



### Product Name:

PakMix® Blacktop Patch

### Distributor:

Consolidated Aggregates  
1205 Palestine Road  
Picayune, MS 39466  
601-798-3158

### Weight and Size (s):

50 lb. bags

**Color:** Black

### Features/Benefits:

- ◆ Pre-blended
- ◆ No mixing necessary - ready to use.
- ◆ Available through Consolidated Aggregates distribution network.

### Applications:

- ◆ Repair of Driveways
- ◆ Repair of Walkways
- ◆ Repair of Parking Areas

### Coverage/Yield for Usage:

One (1) 50# Bag covers approximately 4 square feet by 1" thick or approximately 1/3 (.33) cubic feet when compacted.


### Items you may need:

- ◆ Hand Tamper
- ◆ Shovel or Hoe
- ◆ Lawn Roller

### Preparation:

All surfaces should be clean and free of oil, gas, paint, grease, etc. before applying the material. Remove all loose particles and foreign matter from the area to be repaired.

**Important:** Square edges of hole or crack.



### Mixing Instructions:

Place Pakmix® Blacktop Patch in the area to be repaired. Spread the Blacktop Patch to a level of about 1" higher than the surrounding area and then compact with a hand tamper, lawn roller, or by driving over the patch with a car wheel.

Following prolonged storage Pakmix® Blacktop Patch may feel hard in the bag. This is normal and will not adversely affect the mix. Kneading the material before opening the bag will loosen the material to a workable consistency. In cool and cold weather keep the bags of material in a warm area for at least 24 hours before using.

This product should be installed in accordance of the applicable ASTM standards and the local building codes. Follow traditional industry best practices appropriate for

## PakMix® BLACKTOP PATCH

the application and all weather conditions.

### Clean Up:

Clean-up is easy with soap and water. Rinse the tools before the material hardens.

### Cautions:

AVOID CONTACT WITH SKIN • INJURIOUS TO EYES Pa-kmix® Blacktop Patch contains petroleum asphalt. As with any petroleum-based material, direct contact may irritate the eyes and skin. Wear protective clothing, gloves, and eye protection when using the product. If any material gets into the eyes, rinse immediately and contact a physician. Wash exposed skin areas promptly with water. Do not take internally. EXCLUSION OF INCIDENTAL AND CONSEQUENTIAL DAMAGES Neither the manufacturer nor the retailer of this product shall be liable for any incidental or consequential damages caused by the use of this product.

### Freeze/Thaw Warning:

This product is not air entrained and may be susceptible to freeze/thaw damage. Contact Pakmix® for air entrainment recommendations.

### Safety:

READ AND UNDERSTAND ALL THE INFORMATION ON THE SAFETY DATA SHEET (SDS) BEFORE USING THIS

PRODUCT.

SDS sheets are available at our website [www.consolidatedagg.com](http://www.consolidatedagg.com).

WARNING: Wear protective clothing and equipment.

KEEP OUT OF REACH OF CHILDREN.

