

PakMix® PORTLAND CEMENT

PakMix® Portland Cement (Type I, Type II, Type IL and Type IS Cements) provides the basic performance characteristics of Type I Portland Cement as well as the moderate sulfate resistance and lower heat of hydration characteristic of Type II Portland Cement.



Product Name:

PakMix® Portland Cement
(Type I, Type II, Type IL and Type IS Cements)

Distributor:

Consolidated Aggregates
1205 Palestine Road
Picayune, MS 39466
601-798-3158

Weight and Size (s):

47 lb. and 94 lb. bags and 3000 lb. bulk bags

Color: Gray

Features/Benefits:

◆ Type I/II is an exceptionally versatile basic building material suitable for a variety of concrete construction applications.

Coverage/Yield for Usage:

◆ N/A

Technical Information:

- ASTM C-150 in the Standard Specification for Portland Cement

Mixing Instructions:

Mixing ration for concrete is 1 part cement, 2 parts sand, 3 part gravel.

This product should be installed in accordance of the applicable ASTM standards and the local building codes. Follow traditional industry best practices appropriate for the application and all weather conditions.

Clean Up:

Clean-up is easy with soap and water. Rinse the tools before the material hardens.

Cautions:

Avoid contact with skin and eyes. Contains Portland Cement (CAS #65997-15-1). Freshly mixed cement, mortar, concrete or grout may cause skin injury including severe alkali burns. If exposed, wash skin promptly and repeatedly for 15 minutes and get prompt medical attention. The use of gloves and protective eyewear is recommended.

Freeze/Thaw Warning:

This product is not air entrained and may be susceptible to freeze/thaw damage. Contact Pakmix® for air entrainment recommendations.

Safety:

READ AND UNDERSTAND ALL THE INFORMATION ON THE SAFETY DATA SHEET (SDS) BEFORE USING THIS PRODUCT.

PakMix® PORTLAND CEMENT

SDS sheets are available at our website
www.consolidatedagg.com.

WARNING: Wear protective clothing and equipment.

KEEP OUT OF REACH OF CHILDREN.

