

## PakMix® MORTAR MIX

**PakMix® Mortar Mix** is a specially formulated blend of Masonry cement and fine sand. This product is ideal for use in the laying of brick, block, or stone. All ingredients are thoroughly premixed to ensure maximum strength and workability.

**Product Name:**

PakMix® Mortar Mix

**Distributor:**

Consolidated Aggregate  
1205 Palestine Road  
Picayune, MS 39466  
601-798-3158

**Weight and Size (s):**

60 lb., 80 lb., and 3000 lb. Bulk Bags

**Color:** Gray

**Features/Benefits:**

- ◆ Easy to use for the do it yourselfer on home projects.
- ◆ Simply add water and mix.
- ◆ Cost effective for both small and large projects.
- ◆ Available through Consolidated Aggregates distribution network

**Applications:**

- ◆ Laying Brick
- ◆ Stuccoing
- ◆ Setting Blocks
- ◆ Repairing Chimneys
- ◆ Tuck Pointing
- ◆ Stonework Patching

**Coverage/Yield for Usage:**

- ◆ 60 lb. bag will lay 20 - 8" x 16" blocks or 48 common bricks with a 3/8" joint.
- ◆ Approximately 3/5 cu. ft. wet volume

**Technical Information:**

Compressive Strengths:

- 750 PSI @ 7 days
- Meets or exceeds the strength requirements of ASTM C-270 for Type N Mortar

**Mixing Instructions:**

Pour the estimated amount of Pakmix® Mortar Mix into a clean wheelbarrow, mortar box or similar easy-to-use container. Form a crater with a shovel or hoe in the center of the dry mix. Pour clean water into the crater at a rate of approximately 1 quart per 15 lbs. of dry material. If the mix is too stiff, add more water, 1 cup at a time. The mix should have the consistency of thick batter.

NOTE: Use only when the temperature is 40° F and rising. In cold weather use warm, not hot, water for mixing. Dampen the block or the repair area before applying the new mortar to prevent premature drying of the new material. Keep the new mortar damp for at least 3 days by an occasional fine spray with water.

**Clean Up:**

Clean-up is easy with soap and water. Rinse the tools before the material hardens.

**Cautions:**

Avoid contact with skin and eyes. Contains Portland Cement (CAS #65997-15-1). Freshly mixed cement, mortar, concrete or grout may cause skin injury including severe alkali burns. If exposed, wash skin promptly and

## PakMix® MORTAR MIX

repeatedly for 15 minutes and get prompt medical attention. The use of gloves and protective eyewear is recommended.

### **Warning:**

For structural use or to meet code requirements use Pakmix® Type S Mortar.

### **Freeze/Thaw Warning:**

This product is not air entrained and may be susceptible to freeze/thaw damage. Contact Pakmix® for air entrainment recommendations.

### **Safety:**

READ AND UNDERSTAND ALL THE INFORMATION ON THE SAFETY DATA SHEET (SDS) BEFORE USING THIS PRODUCT.

SDS sheets are available at our website [www.consolidatedagg.net](http://www.consolidatedagg.net).

WARNING: Wear protective clothing and equipment.

KEEP OUT OF REACH OF CHILDREN.

